

**USER INFORMATION****CE 2777**

These products are classed as Category III Personal Protective Equipment (PPE) by the European PPE Regulation (EU) 2016/425 and have been shown to comply with this Regulation through the Harmonized European Standard(s) EN ISO 374-1:2016, EN ISO 374-5:2016 and EN 420:2003+A1:2009

**Product reference:**

Maumo International BV  
Zwaalweg 16  
2991ZC Barendrecht Holland  
Tel 0031(0)1806-99234  
www.gripp-it.nl

**Glove sizes available:** S(7), M(8), L(9), XL(10), XXL(11), XXXL(12)

Notified Body responsible for certification and ongoing conformity:  
SATRA Technology Europe Limited,  
Bracetown Business Park, Clonee, D15YN2P  
Republic of Ireland (Notified Body: 2777)

Storage and transport: When not in use, store the product in a well-ventilated area away from extremes of temperature. Check for damage before use, do not use damaged gloves.

Performance and limitation of use: This product has been tested in accordance with EN ISO 374-1:2016, EN ISO 374-5:2016 and EN 420:2003+A1:2009 and achieved the following performance levels

**EN ISO 374-2:2014**      Air leak      -      Pass      Protection against bacteria and fungi      -      Pass  
Water leak      -      Pass

Tested in accordance with <b>EN ISO 374-5:2016</b>   Virus	The penetration resistance has been assessed under laboratory conditions and relates only to the tested specimen.		
	<b>EN ISO 374-1/Type B</b>		EN16523:2015 Permeation Level
  JKTP	<i>J = n-Heptane</i>	3	30.9%
	<i>K = 40% Sodium Hydroxide</i>	6	-9.4%
	<i>T = 37% Formaldehyde</i>	5	-4.1%
	<i>P = 30% Hydrogen Peroxide</i>	3	-17.0%
<b>Declaration of Conformity</b>	www.gripp-it.com/		

**EN ISO 374-1:2016** Permeation levels are based on breakthrough times as follows:

Performance level	1	2	3	4	5	6
Minimum breakthrough times (mins)	>10	>30	>60	>120	>240	>480

**EN 374-4:2013** Degradation levels indicate the change in puncture resistance of the gloves after exposure to the challenge chemical "This information does not reflect the actual duration of protection in the workplace and the differentiation between mixtures and pure chemicals."

"The chemical resistance has been assessed under laboratory conditions from samples taken from the palm only (except in cases where the glove is equal to or over 400 mm - where the cuff is tested also) and relates only to the chemical tested. It can be different if the chemical is used in a mixture."

"It is recommended to check that the gloves are suitable for the intended use because the conditions at the workplace may differ from the type test depending on temperature, abrasion and degradation."

"When used, protective gloves may provide less resistance to the dangerous chemical due to changes in physical properties. Movements, snagging, rubbing, degradation caused by the chemical contact etc. may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves"

"Before usage, inspect the gloves for any defect or imperfections."

